



OPTIMA 85 B



Suitable for maintenance and thorough cleaning of medium to large size irregularly shaped areas. Extremely compact & maneuverable machine.

- Large capacity solution tank and excellent runtime of upto 4 hours on an average
- Step through driver seat design ensures safety & greater visibility
- Low noise level ensures greater acoustic comfort in noise sensitive environments
- Interchangeable scrubbing heads provide greater operating flexibility
- New age squeegee design gives greater drying efficiency, ease of maintenance and safe.

ULTRA 85/100 B



Excellent operating autonomy, highly effective, economical, robust design scrubbing machine suitable for maintenance and thorough cleaning of medium to large size working, industrial or service areas in general. Step through design ensures excellent accessibility to the driver's seat from either side as well as excellent operating safety.

- Auto speed control when going round a bend
- Electronic float for recovery
- Self test system reduces machine down time.
- Control rotating brushes for efficient scrubbing along walls

C 130 D/B



The robust diesel engine or battery powered heavy duty scrubber drier, suitable for cleaning large industrial areas, commercial premises, railway stations or airports. C130 has four disc brushes, to effectively scrub the floor with an adjustable pressure up to 180kg, and one cylindrical brush to convey dirt into the removable hopper, so that double cleaning action all along its 130 cm working width is ensured. Equipped with electronic check control system.

	OPTIMA 85 B	ULTRA 85 B	ULTRA 100B	C 130 D / B
Working width (mm)	850	850	1000	1300
Disc brushes ø (No.) (mm)	430(2)	430(2)	510(2)	345(4)
Brushes pressure (kg)	85	130(max)	150	130-180
Brushes rpm	140	180	180	220
Productivity @ max fwd speed (m ² /h)	5525	5525	6500	7800
Squeegee width (mm)	1120	1115	1265	1460
Solution tank (Ltr)	160	200	200	360
Recovery tank (Ltr)	160	215	215	380
Brush motor (V/W)	24/500(2)	36/1500	36/2000	36/1125
Suction motor (V/W)	24/320(2)	36/670	36/670	36/1170
Traction motor (V/W)	24/1000	36/1500	36/1500	36/2000
Drive Power	24 V/320 AH	36 V/360 AH	36 V / 360 AH	20 Kw Diesel / (B)36 V / 720 AH
Forward speed (km/h)	0-6.5	0-6.5	0-6.5	0-6
Operating Weight (W/O Batteries)	320 kg	535 kg	556 kg	840 / 840 kg
Dimensions (LxHxW) (mm)	1777x1265x892	1965x1560x895	1965x1560x1045	2250x1880x1340



Comac India Private Limited DLF Tower A, Suite No. 919-920, 9th Floor, Jasola District Centre, New Delhi-110025
For enquiry- cleansolutions@comacindia.com Website: www.comac.it or www.comacindia.com

professional people

Floor care

AUTO SCRUBBER DRIERS



www.comacindia.com



professional people

Floor care range



VISPA 35 E/B



The revolutionary scrubbing machine that scrubs, dries and sanitizes in one pass. Ideal for small, congested areas and maintenance cleaning. Suitable for hotels, hospitals, offices, service stations, recreational facilities, educational institution, etc.

- Highly compact & ergonomic - easy to use
- Cleaning right along the wall - highly maneuverable & productive

ABILA 50 E/B



An extremely maneuverable scrubbing machine with 50 cms width - Is suitable for most areas needing maintenance cleaning. Especially suitable for cleaning in environments like sales points, car repair shops, gyms or health care environments in general. Its extremely low noise levels together with the possibility to use microfibre pads, make it especially suitable for cleaning community areas such as gyms & hospitals or public & private medical institutions

SIMPLA 50 E/B



Simpla 50 is a higher capacity scrubbing machine with 50 cm working width. This machine's user-friendliness is the result of high technological content. Thanks to the tanks' large water capacity and to the extended battery runtime, it is able to perform demanding cleaning tasks (it scrubs and dries up to 1785 sq m/h).

CM 551 E/B



The CM 551 E/B scrubbing machine is designed to carry out daily maintenance operations as fast as possible. It is:

- Provided with key for switching on the machine which restricts from unauthorized persons operating the machine
- Provided with level Indication tube for monitoring the solution level in the solution tank
- Comes with parking brakes
- Provided with HOUR METER for monitoring the machine usage time

INNOVA 55 B



Innova 55 B-ride on scrubbing machine, thanks to its very compact dimensions is able to replace a traditional walk behind scrubbing machine in maintenance cleaning of surfaces up to 3,000 sq. m.

Innova 55 B is a ride on scrubbing machine with automatic traction, available in battery version with single disc brush of 56 cm working width.

It is available in basic version with the technology for consumption optimization and Eco ON/OFF System that automatically stops the brush and water flow when the machine is idle.

TRIPLA 85 B



Tripla 85 B is a Battery driven Ride-On Scrubbing machine with a working width of 85 cm. It is suitable for maintenance cleaning of surfaces upto 5100 sqm per hour and is one of the most safe, productive & user-friendly Scrubbing machine.

- Low centre of gravity for optimum stability. Capable of ramp gradients upto 18%
- Automatic swing-in of the brush head when accidentally impacted
- Automatic squeegee uncoupling when accidentally impacted
- Best manoeuvrability even in narrow spaces thanks to tight turning diameter
- Easy & complete tank sanitizing

	VISPA 35 E/B	ABILA 50 E/B	SIMPLA 50 E/B
Scrubbing width mm	350	500	510
Brush dia mm	1x350	1x500	1x510
Brush Pressure	18/20 kg	20 kg	25-30 kg
Productivity rate	1050 sqm/h	1750 sqm/h	1785 sqm/h
Solution tank	8 ltrs	33 ltrs	50 ltrs
Recovery tank	10 ltrs	40 ltrs	55 ltrs
Brush speed	140 rpm	240/140 rpm	250 rpm
Voltage	230/12 V	230/24 V	230/24 V
Operating Weight (W/o Batteries)	45 kg	70 kg	86 kg
Battery (in B version)	12 V/65 Ah	24 V/100 Ah	24 V/100 Ah
Dimensions in mm (LxHxW)	620x1050x440	1226x960x455	1080x980x555

	CM 551 E/B	INNOVA 55 B	TRIPLA 85 B
Working width (mm)	510	560	850
Brushes ø (No.) (mm)	510(1)	560(1)	430(2)
Brushes pressure(kg)	30-40	30	30-60
Brushes rpm	210	140	170
Squeegee width (mm)	760	705/800	1085
Solution tank(Ltr)	60	65	110
Recovery tank (Ltr)	65	75	125
Productivity @max fwd speed(m ² /h)	2040	3000	5100
Brush motor (V/W)	230/750(E) / 24/560(B)	24/400	24/450(2)
Suction motor (V/W)	230/450(E) / 24/330(B)	24/310	24/310
Traction motor(V/W)	-	24/300	24/400
Forward speed(km/h)	-	0-5	0-6
Batteries (V/Ah)	24/100	24/100	24/225
Operating Weight (W/O Batteries)	150 kg	110 kg	223 kg
Dimensions (LxHxW) (mm)	1418x1039x530	1265x1030x600	1495x1320x680